



Instructions and advices

We congratulate you for choosing Uukha products, and we hope that you will enjoy using them as much as we enjoyed developing them.

Safety:

The bow is a weapon. You should shoot in a range and respect all safety precautions.

Top / bottom limb location:

The poundage markings must be situated in such a way that while the bow is held in a firing position, the writing on the top and bottom limbs would be correctly oriented for reading.

Recommended setup:

AMO draw length	bow	riser	limbs
27"	66"	25"	66"
28"	68"	25"	68"
29"	70"	25"	70"
30"	72"	27"	70"
31"	74"	27"	72"

AMO draw length = the distance in inches between the nock and the pressure button + 1.75 ''.

Weight choice:

Each pair of limbs is weighed with the median adjustment of the tiller screws. The corresponding weight is written on the limbs.

Brace height:


We recommend that you respect the value in a +10mm range. Lower the brace height if you focus on speed, or increase it for stability and comfort.

S-Curve models are very fast. Choose a brace height at the bottom of the range to achieve even more speed.

Bow size	Brace height	Bow size	Brace height
74"	239 mm	64"	205 mm
72"	232 mm	62"	198 mm
70"	225 mm	60"	192 mm
68"	218 mm	58"	186 mm
66"	211 mm	56"	180 mm

String:

The chart indicates the number of strands we advise, depending on the weight measured at your draw length and the string material.



String length leading to advised brace height:

Bow size	S-Curve
74"	1785 mm
72"	1735 mm
70"	1700 mm
68"	1650 mm
66"	1600 mm

Maintenance:

Uukha products are covered with a polyurethane varnish. Simply use water and soap to clean them.

In the event that the varnish is damaged by an impact, be aware that the composite structure is perfectly waterproof and will not absorb water. To preserve the appearance of your product, you can touch up the marred area.

Guarantee:

UUKHA products are guaranteed against any manufacturing defect.

Uukha products are legally guaranteed against manufacturing defects. If you discover a defect despite our controls, please contact your retailer.

More information on www.uukha.com

